

PTU30T Cảm biến kết hợp áp suất, độ ẩm và nhiệt độ

Vaisala Combined Pressure and Temperature Transmitter		PTU300	T	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	PRICE	
1	Transmitter type	PTU30T	for pressure and temperature only	T																									
2	Pressure range	500...1100 hPa 500...1100 hPa 500...1100 hPa 500...1100 hPa 50...1100 hPa 50...1100 hPa	Class A / one sensor Class B / one sensor Class A / two sensors Class B / two sensors One sensor, class B only Two sensors, class B only	1 2 3 4 5 6																									
3	Temperature probe length	2m cable 5 m cable 10 m cable		H J K																									
4	Additional temperature probe	No probe		0																									
5	Display	No display Graphical display with keypad		0 1																									
6	Power supply	10...35 VDC, 24 VAC 10...35 VDC, 24 VAC with galvanic isolation Universal AC power (100...240 VAC) Universal AC power (100...240 VAC) + US power cord Universal AC power (100...240 VAC) + UK power cord Universal AC power (100...240 VAC) + AUS power cord Universal AC power (100...240 VAC) + EURO power cord External US AC-adaptor (for LAN/WLAN interface in USA and Canada)			A B C D E F G K																								
7	Output signal	RS232C only, no analog outputs RS232C + Analog outputs (Ch1 & Ch2, optional Ch3) RS232C + Analog outputs (Ch1 & Ch2, optional Ch3) RS232C + Analog outputs (Ch1 & Ch2, optional Ch3) RS232C + Analog outputs (Ch1 & Ch2, optional Ch3) RS232C + Analog outputs (Ch1 & Ch2, optional Ch3)	4... 20 mA 0... 20 mA 0... 1 V 0... 5 V 0... 10 V	0 1 2 3 4 5																									
8-10	Parameter and scaling for analog output (Ch1, Ch2, Ch3)	No Analog output T (T range: selection in step 11) P (pressure range: selection in step 2) Special Define scale for Ch1: _____ Ch2: _____ Ch3: _____			A C P X X X																								
11	Analog output range for temperature	No temperature output -40...+60 °C -20...+60 °C 0...+60 °C	Mandatory if no analog T outputs selected (-40...+140 °F) (-4...+140 °F) (+32...+140 °F)		A B F K X																								
12	Output format	Standard			1																								
13	Output units	Metric Non-metric			A B																								
14	Optional module	No module Relay output Note: Up to one optional module can be selected RS485 serial interface (galvanically isolated) LAN (Ethernet) interface + 2 m cable (RJ45) Data logger module	Mandatory with two pressure sensors or 3rd analog output Not possible with universal AC power module Not possible with D9-adaptor and 8-pole connectors	0 1 2 4 6																									
15	Cable bushings	Cable gland M20*1.5 Note: The universal AC power must not be connected through the 8-pole connector or D9 adaptor Conduit fitting NPT1/2" 8-pole connector with 5m cable 8-pole counter connector with screw terminals D9-adaptor	spare cable: 212142 spare connector: 212416 Only for RS232C, RS485 and DC supply		A B C D E																								
16	Pressure fitting	Barbed fitting for 1/8" hose Quick connector with shutoff valve for 1/8" hose			1 2																								
17	Transmitter installation	Normal mounting Wall mounting plate Pole installation kit Pole installation kit with Rain Shield DIN rail kit	item: 214829 item: 215108 item: 215109 item: 215094		A B C D E																								
18	Humidity sensor	No humidity sensor			0																								
19	Sensor protection	No sensor protection			A																								
20	Probe installation accessories	No probe installation accessories			0																								
21	User's Guide language	No User's Guide English French Japanese			A B D J																								
22	PC Accessories	No Service cable for PC, RS232 (D9 female connector) MI70LINK software for Windows® with RS232 service cable Service cable for PC, USB MI70LINK software for Windows® with USB service cable	item: 19446ZZ item: 215005 item: 219685 item: 219916	0 1 2 3 4																									
23	Calibration	ISO9001 compliant factory calibration Special calibration	See separate order form service item: HELSPECIALCAL		A X																								
TOTAL																													
QTY																													
TOTAL VALUE																													

Selections in bold are included in the prices of the basic versions.
 Selections in italic are available at an extra price.

Example of order code with typical settings:

PTU300 T 1 H 0 1 A 1 C P B 1 A 0 A 1 A 0 A 0 B 0 A

End customer: _____